



AMP INDUSTRIES

Plot No. 625, Phase 4, GDIC Estate, Naroda, Ahmedabad-382330, Gujarat


STREET LIGHT : SFLD20WSLIM65-68

Essential Parameter

- Light Source Type: Light control
- Lamp Power:20W
- Rated Voltage:AC100-240VAC 50/60Hz
- LED Efficiency:130-145 Lm/W
- Lamp Flux:>90lm/w~140lm/w
- Beam Angle:130°*60°
- CCT:3000-6000K available
- Working Temperature:-40°C-90°C
- Life Span:>50,000hrs
- IP Grade:IP66
- Installation Diameter:60mm



OPTIONAL



Product Other Design Option



Information

- Amp : 0.20A , P.F :> 0.9
- Ta : 45 C , Tc :90 C , Class -I
- Made in India

Illuminance In Different Height Pole

Pole Height	Average Illuminance	Center Illuminance
3m	49.5lux 9.3lux	6
4m	28.2lux	39.5lux
5m	17.9lux	25.1lux
6m	12.5lux	17.5lux

Applicable places

Road lighting of express way, village, township roads, residential areas, parks and factory



STREET LIGHT : SFLD30WSLIM65-68

◆ Essential Parameter

Light Source Type: Light control

Lamp Power:30W

Rated Voltage:AC100-240VAC 50/60Hz

LED Efficiency:130-145 Lm/W

Lamp Flux:>90lm/w~140lm/w

Beam Angle:130°*60°

CCT:3000-6000K available

Working Temperature:-40°C~70°C


Life Span:>50,000hrs

IP Grade:IP66

Installation Diameter:60mm



OPTIONAL



◆ Product Other Design Option



◆ Information

Amp : 0.30A , P.F :> 0.9

Ta : 45 C , Tc : 75 C , Class -I

Made in India

◆ Illuminance In Different Height Pole

Pole Height	Average Illuminance	Center Illuminance
4m	46.3lux	65.9lux
5m	29.9lux	41.9lux
6m	20.9lux	29.3lux
7m	15.3lux	21.4lux

◆ Applicable places

Road lighting of express way,village,township roads,residential areas,parks and factory



STREET LIGHT : SFLD40WSLIM65-68

◆ Essential Parameter

Light Source Type: Light control

Lamp Power:40W

Rated Voltage:AC100-240VAC 50/60Hz

LED Efficiency:130-145 Lm/W

Lamp Flux:>90lm/w~140lm/w

Beam Angle:130°*60°

CCT:3000-6000K available

Working Temperature:-40°C~70°C


Life Span:>50,000hrs

IP Grade:IP66

Installation Diameter:60mm



OPTIONAL



◆ Product Other Design Option



◆ Information

Amp : 0.40A , P.F :> 0.9

Ta : 45 C , Tc : 75 C , Class -I

Made in India

◆ Illuminance In Different Height Pole

Pole Height	Average Illuminance	Center Illuminance
4m	46.4lux	65.9lux
5m	30.2lux	42.3lux
6m	21.2lux	30.3lux
7m	16.1lux	22.3lux

◆ Applicable places

Road lighting of express way,village,township roads,residential areas,parks and factory



STREET LIGHT : SFLD50WSLIM65-68

◆ Essential Parameter

Light Source Type: Light control

Lamp Power:50W

Rated Voltage:AC100-240VAC 50/60Hz

LED Efficiency:130-145 Lm/W

Lamp Flux:>90lm/w~140lm/w

Beam Angle:130°*60°

CCT :3000-6000K available

Working Temperature:-40°C~70°C


Life Span:>50,000hrs

IP Grade:IP66

Installation Diameter:60mm



OPTIONAL



◆ Product Other Design Option



◆ Information

Amp : 0.50A , P.F :> 0.9

Ta : 45 C , Tc : 75 C , Class -I

Made in India

◆ Illuminance In Different Height Pole

Pole Height	Average Illuminance	Center Illuminance
4m	48.2lux	66.9lux
5m	31.2lux	43.2lux
6m	22.9lux	31.8lux
7m	16.8lux	22.9lux

◆ Applicable places

Road lighting of express way,village,township roads,residential areas,parks and factory



STREET LIGHT : SFLD60WSLIM65-68

◆ Essential Parameter

Light Source Type: Light control

Lamp Power:60W

Rated Voltage:AC100-240VAC 50/60Hz

LED Efficiency:130-145 Lm/W

Lamp Flux:>90lm/w~140lm/w

Beam Angle:130°*60°

CCT:3000-6000K available

Working Temperature:-40°C~70°C


Life Span:>50,000hrs

IP Grade:IP66

Installation Diameter:60mm



OPTIONAL



◆ Product Other Design Option



◆ Information

Amp : 0.60A , P.F :> 0.9

Ta : 45 C , Tc : 75 C , Class -I

Made in India

◆ Illuminance In Different Height Pole

Pole Height	Average Illuminance	Center Illuminance
5m	38.8lux	54.2lux
6m	26.4lux	38.7lux
7m	19.2lux	26.7lux
8m	14.4lux	20.9lux

◆ Applicable places

Road lighting of express way,village,township roads,residential areas,parks and factory



STREET LIGHT : SFLD70WSLIM65-68

◆ Essential Parameter

Light Source Type: Light control

Lamp Power:70W

Rated Voltage:AC100-240VAC 50/60Hz

LED Efficiency:130-145 Lm/W

Lamp Flux:>90lm/w~140lm/w

Beam Angle:130°*60°

CCT:3000-6000K available

Working Temperature:-40°C~70°C


Life Span:>50,000hrs

IP Grade:IP66

Installation Diameter:60mm



OPTIONAL



◆ Product Other Design Option



◆ Information

Amp : 0.70A , P.F :> 0.9

Ta : 45 C , Tc : 75 C , Class -I

Made in India

◆ Illuminance In Different Height Pole

Pole Height	Average Illuminance	Center Illuminance
5m	39.9lux	55.9lux
6m	27.9lux	39.8lux
7m	20.4lux	28.6lux
8m	15.7lux	22.3lux

◆ Applicable places

Road lighting of express way,village,township roads,residential areas,parks and factory



STREET LIGHT : SFLD80WSLIM65-68

◆ Essential Parameter

Light Source Type: Light control

Lamp Power:80W

Rated Voltage:AC100-240VAC 50/60Hz

LED Efficiency:130-145 Lm/W

Lamp Flux:>90lm/w~140lm/w

Beam Angle:130°*60°

CCT:3000-6000K available

Working Temperature:-40°C~70°C


Life Span:>50,000hrs

IP Grade:IP66

Installation Diameter:60mm



OPTIONAL



◆ Product Other Design Option



◆ Information

Amp : 0.80A , P.F :> 0.9

Ta : 45 C , Tc : 75 C , Class -I

Made in India

◆ Illuminance In Different Height Pole

Pole Height	Average Illuminance	Center Illuminance
5m	44.1lux	62.7lux
6m	31.2lux	43.9lux
7m	22.8lux	32.4lux
8m	17.7lux	24.1lux

◆ Applicable places

Road lighting of express way,village,township roads,residential areas,parks and factory



STREET LIGHT : SFLD90WSLIM65-68

◆ Essential Parameter

Light Source Type: Light control

Lamp Power:90W

Rated Voltage:AC100-240VAC 50/60Hz

LED Efficiency:130-145 Lm/W

Lamp Flux:>90lm/w~140lm/w

Beam Angle:130°*60°

CCT:3000-6000K available

Working Temperature:-40°C~70°C


Life Span:>50,000hrs

IP Grade:IP66

Installation Diameter:60mm



OPTIONAL



◆ Product Other Design Option



◆ Information

Amp : 0.90A , P.F :> 0.9

Ta : 45 C , Tc : 75 C , Class -I

Made in India

◆ Illuminance In Different Height Pole

Pole Height	Average Illuminance	Center Illuminance
6m	41.8lux	58.5lux
7m	30.4lux	42.9lux
8m	23.5lux	32.9lux
9m	18.5lux	25.9lux

◆ Applicable places

Road lighting of express way,village,township roads,residential areas,parks and factory



STREET LIGHT : SFLD100WSLIM65-68

◆ Essential Parameter

Light Source Type: Light control

Lamp Power:100W

Rated Voltage:AC100-240VAC 50/60Hz

LED Efficiency:130-145 Lm/W

Lamp Flux:>90lm/w~140lm/w

Beam Angle:130°*60°

CCT :3000-6000K available

Working Temperature:-40°C~70°C


Life Span:>50,000hrs

IP Grade:IP66

Installation Diameter:60mm



OPTIONAL



◆ Product Other Design Option



◆ Information

Amp : 0.90A , P.F :> 0.9

Ta : 45 C , Tc : 75 C , Class -I

Made in India

◆ Illuminance In Different Height Pole

Pole Height	Average Illuminance	Center Illuminance
6m	50.3lux	65.9lux
7m	37lux	51.8lux
8m	30.2lux	42.8lux
9m	25.4lux	37.1lux

◆ Applicable places

Road lighting of express way,village,township roads,residential areas,parks and factory



STREET LIGHT : SFLD110WSLIM65-68

◆ Essential Parameter

Light Source Type: Light control

Lamp Power:110W

Rated Voltage:AC100-240VAC 50/60Hz

LED Efficiency:130-145 Lm/W

Lamp Flux:>90lm/w~140lm/w

Beam Angle:130°*60°

CCT:3000-6000K available

Working Temperature:-40°C~70°C


Life Span:>50,000hrs

IP Grade:IP66

Installation Diameter:60mm



OPTIONAL



◆ Product Other Design Option



◆ Information

Amp : 1.10A , P.F :> 0.9

Ta : 45 C , Tc : 75 C , Class -I

Made in India

◆ Illuminance In Different Height Pole

Pole Height	Average Illuminance	Center Illuminance
6m	47.1lux	65.9lux
7m	37lux	51.8lux
8m	30.2lux	42.8lux
9m	24.8lux	38.7lux

◆ Applicable places

Road lighting of express way,village,township roads,residential areas,parks and factory



STREET LIGHT : SFLD120WSLIM65-68

◆ Essential Parameter

Light Source Type: Light control

Lamp Power:120W

Rated Voltage:AC100-240VAC 50/60Hz

LED Efficiency:130-145 Lm/W

Lamp Flux:>90lm/w~140lm/w

Beam Angle:130°*60°

CCT :3000-6000K available

Working Temperature:-40°C~70°C


Life Span:>50,000hrs

IP Grade:IP66

Installation Diameter:60mm



OPTIONAL



◆ Product Other Design Option



◆ Information

Amp : 1.20A , P.F :> 0.9

Ta : 45 C , Tc : 75 C , Class -I

Made in India

◆ Illuminance In Different Height Pole

Pole Height	Average Illuminance	Center Illuminance
6m	47.1lux	65.9lux
7m	37lux	51.8lux
8m	30.2lux	42.8lux
9m	24.8lux	38.7lux

◆ Applicable places

Road lighting of express way,village,township roads,residential areas,parks and factory



STREET LIGHT : SFLD150WSLIM65-68

◆ Essential Parameter

Light Source Type: Light control

Lamp Power:150W

Rated Voltage:AC100-240VAC 50/60Hz

LED Efficiency:130-145 Lm/W

Lamp Flux:>90lm/w~140lm/w

Beam Angle:130°*60°

CCT:3000-6000K available

Working Temperature:-40°C~70°C


Life Span:>50,000hrs

IP Grade:IP66

Installation Diameter:60mm



OPTIONAL



◆ Product Other Design Option



◆ Information

Amp : 1.50A , P.F :> 0.9

Ta : 45 C , Tc : 75 C , Class -I

Made in India

◆ Illuminance In Different Height Pole

Pole Height	Average Illuminance	Center Illuminance
7m	48.2lux	67.4lux
8m	38.4lux	53.9lux
9m	29.8lux	41.6lux
10m	23.5lux	34.7lux

◆ Applicable places

Road lighting of express way,village,township roads,residential areas,parks and factory



STREET LIGHT : SFLD180WSLIM65-68

◆ Essential Parameter

Light Source Type: Light control

Lamp Power:180W

Rated Voltage:AC100-240VAC 50/60Hz

LED Efficiency:130-145 Lm/W

Lamp Flux:>90lm/w~140lm/w

Beam Angle:130°*60°

CCT:3000-6000K available

Working Temperature:-40°C~70°C


Life Span:>50,000hrs

IP Grade:IP66

Installation Diameter:60mm



OPTIONAL



◆ Product Other Design Option



◆ Information

Amp : 1.80A , P.F :> 0.9

Ta : 45 C , Tc : 75 C , Class -I

Made in India

◆ Illuminance In Different Height Pole

Pole Height	Average Illuminance	Center Illuminance
8m	47.1lux	65.9lux
9m	37lux	51.8lux
10m	30.2lux	42.8lux
11m	24.8lux	38.7lux

◆ Applicable places

Road lighting of express way,village,township roads,residential areas,parks and factory



STREET LIGHT : SFLD200WSLIM65-68

◆ Essential Parameter

Light Source Type: Light control

Lamp Power:200W

Rated Voltage:AC100-240VAC 50/60Hz

LED Efficiency:130-145 Lm/W

Lamp Flux:>90lm/w~140lm/w

Beam Angle:130°*60°

CCT :3000-6000K available

Working Temperature:-40°C~70°C


Life Span:>50,000hrs

IP Grade:IP66

Installation Diameter:60mm



OPTIONAL



◆ Product Other Design Option



◆ Information

Amp : 2.0A , P.F :> 0.9

Ta : 45 C , Tc : 75 C , Class -I

Made in India

◆ Illuminance In Different Height Pole

Pole Height	Average Illuminance	Center Illuminance
8m	47.9lux	66.7lux
9m	37.4lux	52.6lux
10m	30.9lux	43.4lux
11m	25.6lux	39.2lux

◆ Applicable places

Road lighting of express way,village,township roads,residential areas,parks and factory



STREET LIGHT : SFLD250WSLIM65-68

◆ Essential Parameter

Light Source Type: Light control

Lamp Power:250W

Rated Voltage:AC100-240VAC 50/60Hz

LED Efficiency:130-145 Lm/W

Lamp Flux:>90lm/w~140lm/w

Beam Angle:130°*60°

CCT :3000-6000K available

Working Temperature:-40°C~70°C


Life Span:>50,000hrs

IP Grade:IP66


Installation Diameter:60mm



OPTIONAL



◆ Product Other Design Option



◆ Information

Amp : 2.5A , P.F :> 0.9

Ta : 45 C , Tc : 75 C , Class -I

Made in India

◆ Illuminance In Different Height Pole

Pole Height	Average Illuminance	Center Illuminance
8m	48.1lux	66.9lux
9m	38.2lux	52.8lux
10m	31.2lux	43.8lux
11m	25.8lux	39.7lux

◆ Applicable places

Road lighting of express way,village,township roads,residential areas,parks and factory



STREET LIGHT : SFLD300WSLIM65-68

◆ Essential Parameter

Light Source Type: Light control

Lamp Power:300W

Rated Voltage:AC100-240VAC 50/60Hz

LED Efficiency:130-145 Lm/W

Lamp Flux:>90lm/w~140lm/w

Beam Angle:130°*60°

CCT :3000-6000K available

Working Temperature:-40°C~70°C


Life Span:>50,000hrs

IP Grade:IP66

Installation Diameter:60mm



OPTIONAL



◆ Product Other Design Option



◆ Information

Amp : 3.0A , P.F :> 0.9

Ta : 45 C , Tc : 75 C , Class -I

Made in India

◆ Illuminance In Different Height Pole

Pole Height	Average Illuminance	Center Illuminance
9m	47.1lux	65.9lux
10m	37lux	51.8lux
11m	30.2lux	42.8lux
12m	24.8lux	38.7lux

◆ Applicable places

Road lighting of express way,village,township roads,residential areas,parks and factory



STREET LIGHT : SFLD350WSLIM65-68

◆ Essential Parameter

Light Source Type: Light control

Lamp Power:350W

Rated Voltage:AC100-240VAC 50/60Hz

LED Efficiency:130-145 Lm/W

Lamp Flux:>90lm/w~140lm/w

Beam Angle:130°*60°

CCT:3000-6000K available

Working Temperature:-40°C~70°C


Life Span:>50,000hrs

IP Grade:IP66

Installation Diameter:60mm



OPTIONAL



◆ Product Other Design Option



◆ Information

Amp : 3.5A , P.F :> 0.9

Ta : 45 C , Tc : 75 C , Class -I

Made in India

◆ Illuminance In Different Height Pole

Pole Height	Average Illuminance	Center Illuminance
9m	47.3lux	66.7lux
10m	38.1lux	52.7lux
11m	32.8lux	43.6lux
12m	25.4lux	37.2lux

◆ Applicable places

Road lighting of express way,village,township roads,residential areas,parks and factory



STREET LIGHT : SFLD400WSLIM65-68

◆ Essential Parameter

Light Source Type: Light control

Lamp Power:400W

Rated Voltage:AC100-240VAC 50/60Hz

LED Efficiency:130-145 Lm/W

Lamp Flux:>90lm/w~140lm/w

Beam Angle:130°*60°

CCT:3000-6000K available

Working Temperature:-40°C~70°C


Life Span:>50,000hrs

IP Grade:IP66


Installation Diameter:60mm



OPTIONAL



◆ Product Other Design Option



◆ Information

Amp : 4.0A , P.F :> 0.9

Ta : 45 C , Tc : 75 C , Class -I

Made in India

◆ Illuminance In Different Height Pole

Pole Height	Average Illuminance	Center Illuminance
9m	46.1lux	64.9lux
10m	36.2lux	50.8lux
11m	28.2lux	40.8lux
12m	22.1lux	35.7lux

◆ Applicable places

Road lighting of express way,village,township roads,residential areas,parks and factory



STREET LIGHT : SFLD450WSLIM65-68

◆ Essential Parameter

Light Source Type: Light control

Lamp Power:450W

Rated Voltage:AC100-240VAC 50/60Hz

LED Efficiency:130-145 Lm/W

Lamp Flux:>90lm/w~140lm/w

Beam Angle:130°*60°

CCT:3000-6000K available

Working Temperature:-40°C~70°C


Life Span:>50,000hrs

IP Grade:IP66


Installation Diameter:60mm



OPTIONAL



◆ Product Other Design Option



◆ Information

Amp : 4.5 A , P.F :> 0.9

Ta : 45 C , Tc : 75 C , Class -I

Made in India

◆ Illuminance In Different Height Pole

Pole Height	Average Illuminance	Center Illuminance
9m	46.2lux	64.2lux
10m	36.3lux	52.3lux
11m	29.9lux	41.9lux
12m	23.4lux	36.7lux

◆ Applicable places

Road lighting of express way,village,township roads,residential areas,parks and factory



STREET LIGHT : SFLD500WSLIM65-68

◆ Essential Parameter

Light Source Type: Light control

Lamp Power:500W

Rated Voltage:AC100-240VAC 50/60Hz

LED Efficiency:130-145 Lm/W

Lamp Flux:>90lm/w~140lm/w

Beam Angle:130°*60°

CCT:3000-6000K available

Working Temperature:-40°C~70°C


Life Span:>50,000hrs

IP Grade:IP66

Installation Diameter:60mm



OPTIONAL



◆ Product Other Design Option



◆ Information

Amp : 5.0 A , P.F :> 0.9

Ta : 45 C , Tc : 75 C , Class -I

Made in India

◆ Illuminance In Different Height Pole

Pole Height	Average Illuminance	Center Illuminance
10m	48.2lux	67.9lux
11m	37.6lux	52.4lux
12m	30.9lux	43.1lux
13m	23.8lux	37.4lux

◆ Applicable places

Road lighting of express way,village,township roads,residential areas,parks and factory



KNOWN A is a professional manufacturer of LED lights and solar products. It combines product R & D, product manufacture and installation service in one. Our products include five hundred varieties and nine series, such as LED street lights, courtyard lights, lawn lights, underground lights, underwater lights, LED lights, wall lights, solar light, solar system and so on. With their good performances, high quality, energy saving and environmental protecting, the products are well sold in more than 7 domestic States and regions, such as U.P., M.P., BIHAR, RAJASTHAN, DELHI, etc.

We are a professional LED light manufacturer which focus on three parts: Solar Led Street Light, Building Decoration Lighting and Solar Power Generation. They are highly appreciated. We've got CE, TUV and ROHS certificates.

Our Enterprise Mission

We provide more energy-efficient, more environmentally friendly lighting to the world.

Our Goal

Let Indian use more energy-efficient, more environmentally friendly lighting, also let people of the world use our lighting products.

Our Values

Serve the customers—we bend ourselves to make all of our customers satisfy and help them to get success. Innovation—we pursue the innovation that is important to our customers and us. Meanwhile we promote it will be realized quickly and efficiently.

Honesty and Integrity—we uphold the trust, honesty and responsibility to the internal or external people. Win Win cooperation—we promote mutual understanding and value the diversity, treating our culture openly and fairly.



AMP INDUSTRIES

Plot No. 625, Phase 4, GDIC Estate, Naroda, Ahmedabad-382330, Gujarat

Follow us on:

